



Determination of Radon and Uranium Concentrations in soil samples Iraqi cities

Heiyam Najy Hady Majeed
Kufa University /Faculty of Education for girls/Physics Dep.
heiyam_najy@yahoo.com

ABSTRACT

In this investigation the concentrations of radon and uranium levels in 180 soil samples distributed in 18 cities in Iraqi Country have been measured using long term technique for alpha particles emission with solid state nuclear track detector type CR-39 .

The maximum concentrations of radon was (261.54Bqm-3) in soil sample No. (18) : Basra city , while the minimum activity was (86.80 Bqm-3) in soil sample No. (6): Salahaddin city. The uranium concentrations in the same cities have been measured in (ppm) unit the maximum concentration was (0.0201) in soil sample No. (18):Basra city , while the minimum activity was (0.0067) in soil sample No. (6):Salahaddin city.

The variable values of radon and uranium concentrations may be mentioned that Iraq cities have variable geologies ,despite the limitation of existing data the observational and experimental data presented here is the first investigation and study provided a basis for the radon and uranium map in whole Iraq.

Keywords

Nuclear track detector; CR-39; Radon and Uranium concentrations; soil



Council for Innovative Research

Peer Review Research Publishing System

Journal of Advances in Physics

Vol 4, No 1

editor@cirworld.com

www.cirworld.com, member.cirworld.com

INTRODUCTION

The polymer Solid State Nuclear Track Detectors (SSNTDs) such as CR-39 and CN-85 are very sensitive to the energetic alpha-particles since they cause intense damage trail as it passing through them . So, CR-39 and CN-85 as well as LR-115(II) are used widely for detecting and measuring the α -particle emitter isotopes such as radon gas [1-7] and Uranium [8,9].The concentration of the radioactive materials is correlated with the number of etched tracks per unit area of the detector surface(tracks density),which can be counted with the aid of an optical microscope. This visual counting method is replaced by the measurement of the optical density [10, 11],or the diminishing in the laser beam intensity as it transmit through the etched SSNTDs [12,13].

In the natural environment, radon element has three radioactive isotopes, namely: ^{222}Rn (3.82 d), ^{220}Rn (55 s) and ^{219}Rn (4 s). Normally, ^{220}Rn and ^{219}Rn and their progenies are neglected when studying “radon problem” [14, 15]. The immediate radon precursor is Radium (^{226}Ra), with a half-life of 1600 years, spread widely, particularly in materials which are made from mineral products. The forerunner of radium is Uranium (^{238}U); which has a half-life of 4.47×10^9 years [16]. Radon is picked up by ground water passing through rocks and soil containing such radioactive substances; it enters water supplies when this water is pumped up a well [17].

Materials and Methods :

Collection of soil samples :180 samples of soil distributed in 18 cities in Iraqi Country were taken from location of study, from depth (5 cm) as 10 samples for each city as shown in fig.(1) . Then the samples were cleaned, dried in an oven at 70°C for 12 hours finally they were powdered and sifted by using special sieve (250 μm in diameter) [15]. which are available in market were analyzed. For each sample about 20 gms of soil was kept in a small clean vial (10 cm height and 2.2 cm diameter) and marked with a proper number for identification. Solid State Nuclear Track Detectors (SSNTD) with sheet thickness 300 μm were used in this study, which is usually known as CR-39 plastic detector [16,17].The detectors were small square pieces of size 1cm \times 1cm covered with plastic properly and hung inside the sample of the vial [18]. The open mouths of vial were closed properly and then preserved in suitable place free from disturbance. After completion of the exposure, these were etched in (6.25 N) NaOH solution at a constant temperature of $70 \pm 10^\circ\text{C}$ for six hours in a constant water bath. After removal, the detectors were etched with a sharp pin simultaneously in a beaker. For immersing a detector in the beaker and to let it stand erect each detector was fixed with a paper clip properly at the bottom of the beaker [19]. The central portion of the detector strips was scanned by using a microscope (kruss-mbl 20000) at a magnification of 400(40x objective and 10x eyepiece). The determinations of the concentrations of alpha particles from radon gas in samples were performed by using CR-39 from the intercast Europe srl company. The alpha tracks per cm^2 in each detector were determined using an optical microscope.

The radon gas concentration in samples was obtained by using the sealed-cup technique as shown in Fig.2.The test tubes were sealed and stored for 85 days (from 1-7-2013 to 23-9-2013).




Fig.(1): Samples of soil distributed in 18 cities in Iraqi Country




Fig.(2): The test tubes were sealed and stored for 85 days

Results and Discussion :

For the purpose of calculating ^{222}Rn concentration levels in soil samples, the radon activity density (C) in the air gap above the soil samples were determined by measuring the tracks density on the detector according to the following relation[20]:

$$C = \frac{\rho}{KT} \dots \dots \dots (1)$$

Where C is the ^{222}Rn concentration in the test tube above the sample measured in (Bq/L), ρ is the surface density of tracks on the exposed detectors (Tr/cm^2), T is the exposure time (85 day) and K is the ^{222}Rn gas diffusion constant [21]. Such that

$$K = \frac{1}{4} r \left(2 \cos \theta_c - \frac{r}{R_\alpha} \right) \dots \dots \dots (2)$$

Where r is the test tube radius (1.1 cm), θ_c is the critical angle for CR-39 (35 degree) and R_α is the range of ^{222}Rn alpha particle in air (4.15 cm) [21]. By substituting r, θ_c and R_α in equation (2) we get:-

$$K = 0.377 \text{ cm} \dots \dots \dots (3)$$

The radon activity density in the soils samples (C_{Rn}) in the test tube was calculated by using a model proposed by Somogyi [22]. According to this model, the number of radon atoms exhaled from the sample surface is equal to the number of radon atoms in the can air above the soil samples multiplied by the probability of decay, which can be written in the following form [22]:

$$C_{\text{Rn}} = \lambda ChT/L \dots \dots \dots (4)$$

where λ is the decay constant of (^{222}Rn) = $7.554 \times 10^{-3} (\text{hr}^{-1})$, h is the distance from the surface of soil in the sample cup to the detector (9.5 cm), T is the exposure time of the sample (2040 hr) and L is the depth of the samples (0.5 cm). The activity of (^{222}Rn) in the soil samples will be calculated in (Bq) unit from the following relation:

$$A_{\text{Rn}} = C_{\text{Rn}} V \dots \dots \dots (5)$$

Where V is the Volume of the sample in the test tube

$$V = \pi r^2 L (\text{m}^3) \dots \dots \dots (6)$$



The experimental results obtained in this work for Radon and Uranium Concentrations levels in different types of soil samples in Iraqi cities are presented in table 1.

Table 1. Radon and Uranium Concentrations in soil samples in Iraqi cities

Samples Name	Samples Numbers	Average C_{Rn} (Bq/m ³)	Average $C_{Rn} \times 10^{-4}$ (Bq)	Average C_U (ppm)
S1:Duhuk	10	140.86	2.68	0.0108
S2:Musel	10	163.70	3.11	0.0126
S3:Erbil	10	165.99	3.15	0.0127
S4:Karkuk	10	197.97	3.76	0.0152
S5:Sulamaniya	10	166.75	3.17	0.0128
S6:Salahaddin	10	86.80	1.65	0.0067
S7: Dayala	10	87.18	1.66	0.0067
S8:Anbar	10	94.41	1.79	0.0072
S9:Baghdad	10	251.27	4.78	0.0193
S10:Wast	10	178.17	3.39	0.0137
S11:Babl	10	124.49	2.37	0.0095
S12:Karbala	10	127.54	2.42	0.0098
S13:Najaf	10	140.48	2.67	0.0108
S14:Kadsia	10	143.91	2.74	0.0110
S15:Masan	10	126.77	2.41	0.0097
S16:Theqar	10	132.87	2.53	0.0102
S17:Muthanaa	10	245.17	4.66	0.0188
S18:Basra	10	261.54	4.97	0.0201
Max.	Total number of samples 180	261.54	4.97	0.0201
Min.		86.80	1.65	0.0067
Average		159.21	3.03	0.0122

The maximum concentration was (261.54Bqm⁻³) in soil sample No. (18): Basra city , while the minimum concentration was (86.80 Bqm⁻³) in soil sample No. (6):Salahaddin city. The uranium concentrations in the same cities have been measured in (ppm) unit the maximum concentration was (0.0201) have been observed in soil sample No. (18):Basra city , while the minimum activity was (0.0067) has been observed in soil sample No. (6):Salahaddin city .

The variable values of radon and uranium concentrations may be mentioned that Iraq cities have variable geologies ,despite the limitation of existing data the observational and experimental data presented here is the first investigation and study provided a basis for the radon and uranium map in whole Iraq.

Conclusion :

In this investigation the concentration of radon in Iraqi country cities soil have been measured. We found that the uranium levels in whole soils samples in this field of study within the acceptable value (11.8 ppm) in addition to the radon concentrations in all soil samples was less than the safety limit .



References :

- [1]Tse.K,Nikezic.D and Yu.K, Effects of UVC irradiation on alpha particle track parameters in CR-39,Rad.Meas.,43,(2008)S98-S101
- [2]Chan.K, Ng.F, Nikezice,D and Yu.K, Bulk and track etch properties of CR-39 SSNTD etched in NaOH/ ethanol, Nucl. Inst. And Meth. In physics research ,B263 (2007) 284-289.
- [3]Ng.C ,Chan.K, Li,W,Tse.A,Fong.W,Cheung.T and Yu.K, Biocompatibility enhancement of chemically etched CR-39SSNTDs through superficial pore formation by alpha particle irradiation,Rad.Meas.43,(2008),S537-S540
- [4] Mahmood .A,Bashir.S,US-Salam.A and UL-Hag.F, Track Registration Characteristics of low energy protons in cellulose nitrate (CN-85) ,Turk J Phys.,28 ,(2004) ,283-288
- [5] Zaki .M,Abdel-Naby.A and Ahmed.A Single sheet identification method of heavy charged particles using solid state nuclear track detectors, Ramana J of physics ,69,(2007),191-198
- [6] Durrani, S.A., Ilic, R. (Eds.), Radon Measurements by Etched Track Detectors: Application to Radiation Protection, Earth Sciences and the Environment. World Scientific, Singapore.(1997)
- [7] Abumurad, K.M., Atallah, M., Kullab, M.K., Ismail, A., Determination of radon soil concentration levels in the Governorate of Irbid, Jordan. Radiat. Meas. 28. (1997b) 585–588.
- [8]Abumurad, K. M., Al-Tamimi, M., Emanation power of radon and its concentration in soil and rocks. Radiation Measurements34(2001)423–426.
- [9] Heiyam. N, Ali . K, Natural Radioactivity Measurement in Soil Samples from the new Kufa University location, Iraq, Journal of advance in physics,3,(2013),232-240. [10] Gruber, V., Maringer, F.J., Andstetter, C. L., Radon and other natural radionuclide's in drinking water in Austria: Measurement and assessment, Applied Radiation and Isotopes 67 (2009) 913–917
- [11] Risk Assessment of Radon in Drinking Water, Committee on Risk Assessment of Exposure to Radon in Drinking Water, National Research Council, 296 pages, 6 x 9, (1999)
- [12] EPA, U.S. Environmental Protection Agency, 1991
- [13] EUROPEAN COMMISSION, Commission Recommendation of 20 December 2001 on the protection of the public against exposure to radon in drinking water, 2001/982/Euratom (2001)
- [14] Yousuf, R. M., Husain, M. M., and Najam., L. A., Measurement of Radon -222 Concentration Levels in Spring Water in Iraq. Volume 2, Number 2, Jordan Journal of Physics, (2009) pp. 89-93.
- [15] Otton, J.K., "The geology of radon: U.S.Geological Survey", (General Interest Publications of the U.S. Geological Survey, 1992) p28.
- [16] Durrani, S. A., and Bull, R. K., "Solid state Nuclear Track Detector Principle, Method and Applications", Internatinal Series in Natural Philosophy, Volume-III,1987.
- [17]Gamboa, Estisona, Moreno, A. Golzari, J. I., and Costillo,F., " Nuclear Tracks and Measurement" 1(1984) 443-445.
- [18] Paul J. Early, Dabsnm, Abmp, D. Bruce Sodee. "Principle and Practice of Nuclear Medicine", 2nd edition, Mosby, Year Book 1995.
- [19] Subba Ramu M. C., Defense Science 42(1992)219.
- [20] Hamza, V. Z., Mohankumar, M. N., Cytogenetic damage in human blood lymphocytes exposed in vitro to radon, Mutation Research,661, (2009) pp.1-9.
- [21] Barillon, R., Klein, D., Chambaudet, A.and Devillarde, C., Nucl. Tracks Radiat. Meas. 22(1-4) (1993) 281.
- [22] Somogi. G., Hafez. A., Hunyadi I. and Toth- Szilagyi M. Measurement of exhalation and diffusion parameters of radon in solids by plastic track detectors. Nucl. Track Radiat. Meas. 12,1-6,(1986) 701-704.